

Giada F110D

Bay Trail Fanless Signage Player



Features

- ◆ Intel® Celeron J1900/N2807 Processors
- ◆ 1 x SO-DIMM DDR3L, Up to 8GB
- ◆ Two Independent Displays VGA+HDMI
- ◆ 1 x 2.5" SATA, 1 x mSATA, 1 x TF Card Reader
- ◆ 1 x USB3.0, 4 x USB2.0, 2 x RS232
- ◆ 2 x RJ45, 1 x Mini-PCle for WiFi/BT/3G/4G, 1 x SIM Slot

Specifications

RoHS CE FCC



		F110D
Processor	CPU	Intel® Celeron N2807
	Frequency	1.58 GHz (Up to 2.16 GHz)
	BIOS	AMI Source Code
	Chipset	SOC
Memory	Type	DDR3L-1333 MHz
	Socket	1 x SO-DIMM
	Max Size	8GB
Graphics	GPU	Intel® HD Graphics
	Graphic Engine	DirectX 11.1, OpenGL 3.0, OCL 1.1, OpenGL ES 2.0
	HDMI	1 x HDMI (Max. 1920 x 1080 @60Hz)
	VGA	1 x VGA (Max. 2048 x 1280 @60Hz)
Network	Controller #1	Realtek 8111F Gigabit Ethernet
	Controller #2	Realtek 8111F Gigabit Ethernet
	Interface	2 x RJ45
I/O	USB	1 x USB 3.0, 4 x USB 2.0
	Display Interface	1 x VGA, 1 x HDMI
	LAN	2 x RJ45
	Serial Port	2 x RS232
	Audio	1 x MIC-IN, 1 x AUDIO OUT & SPDIF
	Mini-PCle#1	1 x Full-size Mini-PCle for mSATA
	Mini-PCle#2	1 x Full-size Mini-PCle for WiFi/BT/3G/4G
	SIM	1 x SIM Slot
	JAHC Switch	1
	LED Indicators	1 x HDD LED, 1 x Power LED
Storage	SATA	1 x 2.5" SATA
	mSATA	1 x Full-size mSATA
	Card Reader	1 x TF Card Reader
JAHC Tech	WatchDog Timer	0~255 Second Time Out Support
	Auto Power On	Power Activated Automatically Start
	RTC	Set Up Independently Every day, A Week as a Cycle
	Remote Control	By IR Controller for Power On
	Wake On Lan	Supported
Operation System	Windows	Windows 7/8.1/10
	Linux	Supported

		F110D
Power	Power Type	DC-IN
	Power Adapter	19V/2.1A
Mechanical	Dimensions (W x D x H)	189.6mm x 148.3mm x 26mm
	Fanless	Yes
	Construction	Metal
	Mounting(Optional)	Desk/Wall Mounting and VESA Mounting Kit (JZ183)
	Color	Black
Environment	Operating Temperature	0°C ~ 40°C (32 ℉ ~ 104 ℉) at 0.7m/s Air Flow
	Relative Humidity	95% @ 40°C (non-condensing)
Certification	Certification	CE, FCC Class B, CCC

