



## Thermal Receipt Printer

# XP-C2008

- Water proof, oil proof , dust proof design
- Fast and versatile printing up to 300mm per second
- Wifi, Bluetooth option
- Drop in paper loading and with auto cutter



# XP-C2008

## Thermal Receipt Printer



<b>Model</b>	<b>XP-C2008</b>
<b>Printing method</b>	Direct thermal
<b>Printing paper</b>	79.5±0.5mm×φ80mm
<b>Print width</b>	72mm/ 76mm/ 80mm/ 64mm/ 48mm/ 52mm
<b>Column capacity</b>	576 dots/line or 512 dots/line
<b>Printing speed</b>	300 mm/s Max.
<b>Interface</b>	USB+Serial+Lan/USB+Parallel (Optional : WIFI/Bluetooth)
<b>Line spacing</b>	3.75mm (Adjustable by commands)
<b>Column number</b>	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
<b>Character size</b>	ANK, Font A: 1.5×3.0mm(12×24 dots) Font B: 1.1×2.1mm(9×17 dots) Chinese, traditional Chinese:3.0×3.0mm(24×24 dots)
<b>Cutter</b>	
<b>Auto cutter</b>	Partial
<b>Barcode Character</b>	
<b>Extension character sheet</b>	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / Pc858 / IranII / Latvian / Arabic / PT151(1251)
<b>Barcode types</b>	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/CODE93/CODE128
<b>2D Barcode</b>	QR CODE / PDF417
<b>Input buffer</b>	2048 Kbytes
<b>NV Flash</b>	256 Kbytes
<b>Power</b>	
<b>Power adaptor</b>	Input: AC 100-240V/50~60Hz; Output: DC 24V/2.5A
<b>Printer input</b>	DC 24V/2.5A
<b>Cash drawer</b>	DC 24V/1A
<b>Physical characteristics</b>	
<b>Weight</b>	1.70 Kg
<b>Dimensions</b>	190×145×150mm (D×W×H)
<b>Environmental Requirements</b>	
<b>Work environment</b>	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
<b>Storage environment</b>	Temperature(-10 ~ 60°C) humidity(10 ~ 90%)
<b>Reliability</b>	
<b>Cutter life</b>	1.5 million cuts
<b>Printer head life</b>	150Km
<b>Software</b>	
<b>Emulation</b>	ESC/POS
<b>Driver</b>	Windows/JPOS/ OPOS/Linux/Android/Mac
<b>Utility</b>	Windows & Linux test Utility
<b>SDK</b>	iOS/Android/Windows

